

ASCO™ Solenoid Valves

2 way, NC/NO, Direct Operated, 1/8" or 1/4" Tapped

2/2
Series
256

Features & Benefits

- Wide range of flow and pressure ratings
- Quick disassembly of core tube for easy maintenance of internal parts
- Standard disc seal made of FPM, EPDM, NBR, RUBY suitable for a wide range of operating temperatures and compatible with many fluids
- Standard manual operator allows an easy installation (1/8" version only)
- AC/DC interchangeability of the solenoid without disassembly of the valve (1/8" version only)
- UL429 and EN 60335 certified
- NSF 169 and EC 1935 / 2004 certified see "15-DIGIT PRODUCT CODE"
- Compact and low weight valve
- The solenoid valves satisfy all relevant EU and EAC directives

General

Differential pressure	See «SPECIFICATIONS» [1 bar = 100 kPa]
Ambient temperature range	-10°C to +60°C (14°F to 140°F)
Maximum viscosity	40 cSt (mm²/s)
Response time	10 - 20 ms (1/8" version) 20 - 70 ms (1/4" version)

fluids (*)	temperature range (TS) ⁽¹⁾	materials (*)
air, inert gas, water, oil	0°C to +130°C (32°F to 266°F)	FPM (fluoroelastomer)
hot water and steam ⁽²⁾	-10°C to +170°C (14°F to 338°F)	RUBY disc (FPM seal)
air, inert gas, water hot water and steam ⁽²⁾	-10°C to +140°C (14°F to 284°F)	EPDM (ethylene propylene diene monomer)
air, inert gas, water, oil	-10°C to +90°C (14°F to 194°F)	NBR (nitrile)
refrigerating fluids	-10°C to +90°C (14°F to 194°F)	CR70N (chloroprene) (HNBR seal)

Materials in contact with fluid

(*) Ensure that the compatibility of the fluids in contact with the materials is verified

Body	Brass or stainless steel, AISI 316
Shading coil	Copper
Core tube	Stainless steel
Core and plugnut	Stainless steel
Springs	Stainless steel
Seal	FPM or EPDM or NBR or HNBR
Disc	FPM or EPDM or RUBY or NBR or CR70N
Seat	Brass or Stainless Steel AISI 303

Electrical characteristics

Coil insulation class	F (H - approval pending)
Connector	Spade plug (cable Ø 6-8 mm or Ø 6-10 mm)
Connector specification	DIN 43650, 11 mm, industry standard B (type 01) or ISO 4400 / EN 175301-803, form A (type 02)
Electrical safety	IEC 335
Electrical enclosure protection	Moulded IP67 (EN 60529) with plug-connector
Standard voltages	DC (=) : 12 - 24V (+10% -5%)
(Other voltages and frequencies on request)	AC (~) : 24V/50-60 Hz - 110V/50 Hz (120 V/60Hz) 230V/50-60 Hz (+10% -15%)

operator ambient temperature range (TS)	power ratings		replacement coil			Type	
	holding		hot/cold		=		
	~		~				
°C (°F)	(VA)	(W)	(W)	120 V/60 Hz, 110 V/50 Hz	230 V /50-60 Hz	24 V DC	
-10 to +60 (14 to 140)	4.5	3	3.5	533534-024	533534-003	533534-001	01
	-	-	5	-	-	533534-002	
	8	6	-	-	533534-023	-	02
	-	-	5	-	-	533593-001	
	14	9	9	533593-020	533593-003	533593-002	
	-	-	5.5	-	-	511952-006	03






Options

- NSF 169, EC 1935 / 2004 approval, EPDM/FPM disc and seal (Food Grade), RUBY disc, stainless steel seat
- The use of rigid sealings (RUBY) with gaseous fluids implies a slight leakage, generally limited at 2 scc/min at 1 bar pressure (0.002 l/min).

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

⁽¹⁾ The minimum ambient temperature of the solenoid valve is determined by the limitations of minimum temperature indicated.

⁽²⁾ Steam only for 1/4" version with stainless steel seat or body.



Specifications ⁽¹⁾

Specifications ⁽¹⁾															15-DIGIT PRODUCT CODE											
pipe size	orifice size	flow coefficient Kv		operating pressure differential bar (psi)						power coil (W)		thread type	dimensions / type ⁽²⁾	brass	stainless steel	options		voltage code								
				min.	max. (PS)											without manual operator	with manual operator	230 V/50-60 Hz	110V/50 Hz (120 V / 60 Hz)	24V/50-60 Hz	12 V/DC	24 V/DC				
					air (*)	water (*)	oil (*)																			
	mm (in)	m ³ /h (Cv)	(l/min)	~	=	~	=	~	=	~	=															
NC - Normally closed, FPM disc and seal																										
1/8	1.2 (3/64)	0.051 (0.06)	0.85	0	30 (435)	20 (290)	30 (435)	20 (290)	30 (435)	20 (290)	3	3.5	G	01	G256C134S1	G256C144S1	V00	V01								
					-	26 (377)	-	26 (377)	-	26 (377)	-	5	G	01	G256C149S1	G256C159S1										
					-	26 (377)	-	26 (377)	-	26 (377)	-	5	NPT	01	G256C149S1	G256C159S1										
	1.6 (1/16)	0.08 (0.09)	1.33	0	30 (435)	12 (174)	30 (435)	12 (174)	30 (435)	12 (174)	3	3.5	G	01	G256C135S1	G256C145S1										
					-	16 (232)	-	16 (232)	-	16 (232)	-	5	G	01	G256C150S1	G256C160S1										
					-	16 (232)	-	16 (232)	-	16 (232)	-	5	NPT	01	G256C150S1	G256C160S1										
	2 (5/64)	0.12 (0.14)	1.99	0	15 (218)	6 (87)	15 (218)	6 (87)	15 (218)	6 (87)	3	3.5	G	01	G256C136S1	G256C146S1										
					-	7 (102)	-	7 (102)	-	7 (102)	-	5	G	01	G256C151S1	G256C161S1										
					-	7 (102)	-	7 (102)	-	7 (102)	-	5	NPT	01	G256C151S1	G256C161S1										
	2.4 (3/32)	0.14 (0.16)	2.32	0	13 (189)	4 (58)	13 (189)	4 (58)	13 (189)	4 (58)	3	3.5	G	01	G256C137S1	G256C147S1										
					-	6 (87)	-	6 (87)	-	6 (87)	-	5	G	01	G256C152S1	G256C162S1										
					-	6 (87)	-	6 (87)	-	6 (87)	-	5	NPT	01	G256C152S1	G256C162S1										
	3.2 (1/8)	0.18 (0.21)	2.99	0	7 (102)	2 (29)	7 (102)	2 (29)	7 (102)	2 (29)	3	3.5	G	01	G256C138S1	G256C148S1										
					-	3 (44)	-	3 (44)	-	3 (44)	-	5	G	01	G256C153S1	G256C163S1										
					-	3 (44)	-	3 (44)	-	3 (44)	-	5	NPT	01	G256C153S1	G256C163S1										
1/4 ⁽³⁾	1.6 (1/16)	0.10 (0.11)	1.59	0	30 (435)	30 (435)	30 (435)	30 (435)	30 (435)	30 (435)	-	5	G*	02	G256C102S1	G256C111S1	V00	-	FH	F0	FQ	F3	F1			
					-	18 (261)	-	18 (261)	-	18 (261)	-	5	G*	02	G256C102S1	G256C111S1										
					-	18 (261)	-	18 (261)	-	18 (261)	-	5	NPT	02	G256C102S1	G256C111S1										
	2.4 (3/32)	0.18 (0.21)	2.99	0	20 (290)	20 (290)	20 (290)	20 (290)	20 (290)	20 (290)	9	9	G*	02	G256C119S1	G256C127S1										
					-	18 (261)	-	18 (261)	-	18 (261)	-	5	G*	02	G256C104S1	G256C113S1										
					-	18 (261)	-	18 (261)	-	18 (261)	-	5	NPT	02	G256C104S1	G256C113S1										
	3.2 (1/8)	0.30 (0.35)	5.03	0	15 (218)	12 (174)	15 (218)	12 (174)	15 (218)	12 (174)	9	9	G*	02	G256C121S1	G256C129S1										
					-	6 (87)	-	6 (87)	-	6 (87)	-	5	G*	02	G256C106S1	G256C115S1										
					-	6 (87)	-	6 (87)	-	6 (87)	-	5	NPT	02	G256C106S1	G256C115S1										
	4.5 (11/64)	0.40 (0.46)	6.64	0	8 (116)	6 (87)	8 (116)	6 (87)	8 (116)	6 (87)	9	9	G*	02	G256C123S1	G256C131S1										
					-	3 (44)	-	3 (44)	-	3 (44)	-	5	G*	02	G256C107S1	G256C116S1										
					-	3 (44)	-	3 (44)	-	3 (44)	-	5	NPT	02	G256C107S1	G256C116S1										
	5 (13/64)	0.48 (0.55)	7.92	0	5 (73)	4 (58)	5 (73)	4 (58)	5 (73)	4 (58)	9	9	G*	02	G256C124S1	G256C132S1										
					-	2 (29)	-	2 (29)	-	2 (29)	-	5	G*	02	G256C124S1	G256C132S1										
					-	2 (29)	-	2 (29)	-	2 (29)	-	5	NPT	02	G256C124S1	G256C132S1										
5 (13/64)	0.48 (0.55)	7.92	0	5 (73)	4 (58)	5 (73)	4 (58)	5 (73)	4 (58)	9	9	G*	02	G256C108S1	G256C117S1											
				-	2 (29)	-	2 (29)	-	2 (29)	-	5	G*	02	G256C108S1	G256C117S1											
				-	2 (29)	-	2 (29)	-	2 (29)	-	5	NPT	02	G256C108S1	G256C117S1											
5 (13/64)	0.48 (0.55)	7.92	0	5 (73)	4 (58)	5 (73)	4 (58)	5 (73)	4 (58)	9	9	G*	02	G256C125S1	G256C133S1											
				-	2 (29)	-	2 (29)	-	2 (29)	-	5	G*	02	G256C125S1	G256C133S1											
				-	2 (29)	-	2 (29)	-	2 (29)	-	5	NPT	02	G256C125S1	G256C133S1											

⁽¹⁾ All performances are referred to Ambient Temperature = +60°C.

⁽²⁾ For dimensions, see drawing(s) for each construction type on the following page(s).

⁽³⁾ Steam: .RUBY Sealing PS max. 8 bar (max. temperature of fluid 170°C)

.EPDM Sealing PS max. 4 bar (max. temperature of fluid 140°C)

.FPM Sealing PS max. 2.8 bar (max. temperature of fluid 130°C)

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

Specifications ⁽¹⁾

Specifications ⁽¹⁾														15-DIGIT PRODUCT CODE											
pipe size	orifice size	flow coefficient Kv		operating pressure differential bar (psi)						power coil (W)		thread type	dimensions / type ⁽²⁾	brass	stainless steel	options		voltage code							
				max. (PS)												without manual operator	with manual operator	230 V/50-60 Hz	110 V/50 Hz (120 V / 60 Hz)	24 V/50-60 Hz	12 V/DC	24 V/DC			
				air (*)		water (*)		oil (*)																	
	mm (in)	m³/h (Cv)	(l/min)	min.	~	=	~	=	~	=	~					=									
NO - Normally open, FPM disc and seal																									
1/8	1.2 (3/64)	0.05 (0.06)	0.85	0	17 (247)	-	17 (247)	-	17 (247)	-	6	-	G 01	G256C230S1	G256C242S1	V00	-	FH	F0	FQ	F3	F1			
		0.05 (0.06)	0.83	0	-	17 (247)	-	17 (247)	-	17 (247)	-	5.5	NPT 01	8256C230S1	8256C242S1										
													G 03	G256C246S1	G256C250S1										
													NPT 03	8256C246S1	8256C250S1										
	1.6 (1/16)	0.08 (0.09)	1.33		17 (247)	-	17 (247)	-	17 (247)	-	6	-	G 01	G256C231S1	G256C243S1										
														NPT 01	8256C231S1								8256C243S1		
															G 03								G256C247S1	G256C251S1	
															NPT 03								8256C247S1	8256C251S1	
NO - Normally open, FPM disc and seal, stainless steel seat																									
1/4 ⁽³⁾	3.2 (1/8)	0.3 (0.35)	5.0	0	4 (58)	4 (58)	4 (58)	9	9	G 02	G256C216S1	-	9DQ	-	FH	F0	FQ	F3	F1						
										NPT 02	8256C216S1	-													
NO - Normally open, FPM disc and seal (Food Grade), stainless steel seat + NFS + EC 1935 / 2004																									
1/4 ⁽³⁾	3.2 (1/8)	0.3 (0.35)	5.0	0	4 (58)	4 (58)	4 (58)	9	9	G 02	G256C216S1	-	9DH	-	FH	F0	FQ	F3	F1						
										NPT 02	8256C216S1	-													

⁽¹⁾ All performances are referred to Ambient Temperature = +60°C.


⁽²⁾ For dimensions, see drawing(s) for each construction type on the following page(s).

⁽³⁾ Steam: FPM Sealing PS max. 2.8 bar (max. temperature of fluid 130°C)

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

Product selection guide

Configurator - CAD Files



Repair Kits and Service Parts - Spare Parts Kits

Spare parts kits no. (*)														
		EPDM Disc and Seal	FPM Disc and Seal	NBR Disc and Seal	-	-	-	-	-	-	-	-	-	-
NC - Normally closed - 1/4" - AC (~)														
256C119/121/123/ 124/125/127/129/ 129/131/132/133	M200706	E00	V00	N00	-	-	-	-	-	-	-	-	-	-
NC - Normally closed - 1/4" - DC (=)														
256C119/121/123/ 124/125/127/129/ 129/131/132/133	M200714	E00	V00	N00	-	-	-	-	-	-	-	-	-	-
NO - Normally open - 1/4" - AC (~) / DC (=)														
256C216	M200716	-	-	-	-	-	-	-	-	-	-	-	-	-
		EPDM Disc and Seal (Food Grade) + NSF + EC 1935 / 2004 + Stainless Steel Seat	FPM Disc and Seal (Food Grade) + NSF + EC 1935 / 2004 + Stainless Steel Seat	RUBY Disc (FPM Seal) + Stainless Steel Seat + NSF + EC 1935 / 2004	-	-	RUBY Disc (FPM Seal) + NSF + EC 1935 / 2004	EPDM Disc and Seal (Food Grade) + NSF + EC 1935 / 2004	FPM Disc and Seal (Food Grade) + NSF + EC 1935 / 2004	EPDM Disc and Seal + Stainless Steel Seat	FPM Disc and Seal + Stainless Steel Seat	RUBY Disc (FPM Seal) + Stainless Steel Seat	CR70N Disc (HNBR Seal)	RUBY Disc (FPM Seal)
NC - Normally closed - 1/4" - AC (~)														
256C119/121/123/ 124/125/127/129/ 129/131/132/133	M200706	9DF	9DH	-	-	-	-	9CK	9CM	9DP	9DQ	-	J00	X00
256C106/107/115/ 116/123/124/131/ 132	M200707	-	-	9ED	-	-	9CJ	-	-	-	-	9DY	-	-
NC - Normally closed - 1/4" - DC (=)														
256C119/121/123/ 124/125/127/129/ 129/131/132/133	M200714	9DF	9DH	-	-	-	-	9CK	9CM	9DP	9DQ	-	J00	X00
256C106/107/115/ 116/123/124/131/ 132	M200715	-	-	9ED	-	-	9CJ	-	-	-	-	9DY	-	-
NO - Normally open - 1/4" - AC (~) / DC (=)														
256C216	M200716	-	9DH	-	-	-	-	-	-	-	9DQ	-	-	-

Installation

- The solenoid valves can be mounted in any position without affecting operation
- Solenoid valves have 2 mounting holes in body
- Thread connection “G” applicable for 1/8, have standard thread according to ISO 228/1
- Thread connection “8” have standard thread = NPT (SAE 71051)
- Installation/maintenance instructions are included with each valve


Dimensions mm (inches), Weight kg (Lbs)

Configurator - CAD Files



TYPE 01
Electrical interface “S1”
Coil size 20 mm - Thermoplastic moulded
IEC 335 / DIN 43650
IP67

NC (1/8”): 256C134 to163



- ① 2 mounting holes:
M3 dia., through holes (0.12 inch dia.)
- ② Manual operator location

size 20		A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	weight ⁽¹⁾	
G256C134..G256C163	mm	61.9	30.5	16.5	33.2	20	44.6	54.9	69.7	64.8	19.9	24.95	9	18	15	7.5	0.116	kg
8256C134..8256C163	(in)	2.44	1.20	0.65	1.31	0.79	1.76	2.16	2.74	2.55	0.78	0.98	0.35	0.71	0.59	0.30	0.2556	(Lbs)

⁽¹⁾ Incl. coil(s) and connector(s).

Dimensions mm (inches), Weight kg (Lbs)

Configurator - CAD Files



TYPE 02


Electrical interface "S1"

Coil size 30 mm - Thermoplastic moulded

IEC 335 / ISO 4400

IP67

NC (1/4"): 256C102 to 133



- ① 2 mounting holes:
M4 dia., through holes (0.16 inch dia.)


size 30		A	B	C	D	E	F	G	H	J	K	M	N	P	Q	weight ⁽¹⁾	
G256C100..G256C133	mm	66.3	36.6	21.6	43	30	60	70.5	86.7	72.6	28.5	12	24	22	11	0.3	kg
8256C100..8256C133	(in)	2.61	1.44	0.85	1.69	1.18	2.36	2.78	3.40	2.86	1.12	0.47	0.94	0.87	0.43	0.661	(Lbs)

⁽¹⁾ Incl. coil(s) and connector(s).

Dimensions mm (inches), Weight kg (Lbs)

Configurator - CAD Files

NO (1/4"): 256C201 to 221



1 2 mounting holes:
 M4 dia., depth 8 mm (0.16 inch dia., depth 0.31 inch)

size 30		A	B	C	D	E	F	G	H	J	K	M	N	P	Q	weight ⁽¹⁾	
G256C200..G256C221	mm	66.3	36.6	21.6	42	30	61.6	84.4	98.5	72.1	31.4	12	24	24	12	0.34	kg
8256C200..8256C221	(in)	2.61	1.44	0.85	1.65	1.18	2.42	3.32	3.88	2.80	1.24	0.47	9.94	0.94	0.47	0.75	(Lbs)

⁽¹⁾ Incl. coil(s) and connector(s).


Dimensions mm (inches), Weight kg (Lbs)

Configurator - CAD Files



TYPE 03
Electrical interface "S1"
Coil size 30 mm - Thermoplastic moulded
IEC 335 / ISO 4400
IP67

NO (1/8"): 256C246 to 253



① 2 mounting holes:
M3 dia., through holes (0.12 inch dia.)

size 30		A	B	C	D	E	F	G	H	J	K	M	N	P	Q	weight ⁽¹⁾	
G256C246..G256C253	mm	67.7	38	23.3	33.2	29.7	45.7	52.7	71.2	69.4	19.9	9	18	15	7.5	0.20	kg
8256C246..8256C253	(in)	2.66	1.49	0.92	1.31	1.18	1.8	2.07	2.8	2.73	0.79	0.35	0.70	0.59	0.29	0.44	(Lbs)

⁽¹⁾ Incl. coil(s) and connector(s).