

ASCO™ Solenoid Valves

For High Pressure Fluids

Direct Operated, 1/8" or 1/4" tapped, 15 mm Compression Fittings

2/2 NC-NO

Series

262

- High operating pressure
- RoHS compliance
- AC/DC interchangeability of the coil possible only for NC (10,1 W/11,6 W and 17,1 W/22,6 W)
- Valves do not require a minimum operating pressure
- Large selection of seal materials providing wide chemical compatibility
- Compliance with UL and CSA standards
- The solenoid valves satisfy all relevant EU directives

General

Differential pressure

See «SPECIFICATIONS» [1 bar = 100 kPa]

Maximum viscosity

65 cSt (mm²/s)

Response time

5 - 25 ms

fluids (*)	temperature range (TS)	seal materials (*)
air, inert gas, water, oil	-25°C to +80°C	NBR (nitrile)
	0°C to +60°C	UR (cast urethane)

Materials in contact with fluid

(*) Ensure that the compatibility of the fluids in contact with the materials is verified

Body	Brass or Stainless steel, AISI 304
Shading coil	Copper or Silver
Core tube	Stainless steel, AISI 305
Core and plugnut	Stainless steel, AISI 430F
Springs	Stainless steel, AISI 302
Seal	NBR
Disc	NBR or UR
Disc holder (NO function)	PA

Electrical characteristics

Coil insulation class

F (AC) or H (DC)

Connector

Spade plug (cable Ø 6-10 mm)

Connector specification

ISO 4400 / EN 175301-803, form A

Electrical safety

IEC 335

Electrical enclosure protection

Moulded IP65 (EN 60529)

Standard voltages

DC (=) : 24V - 48V

(Other voltages and 60 Hz on request)

AC (-) : 24V - 48V - 115V - 230V/50 Hz

operator ambient temperature range (TS)	power ratings				replacement coil ⁽¹⁾	
	inrush ~	holding ~	hot/cold =		~	=
(°C)	(VA)	(VA)	(W)	(W)	230 V/50 Hz	24 V DC
-25 to +55	30	16	8,1	7,7/10,6	238213-059	238513-006
	45	20	11,1	12,5/18,6	238213-157	238513-106
	50	25	10,1	8,5/11,6	238613-059	238913-006
	70	40	17,1	15,1/22,6	238613-159	238913-106


⁽¹⁾ All 238 basic numbers are UL & CSA approved and marked with the UR (recognised component) & CSA logos.

Options


- Seals and disc (τ) ⁽²⁾
(fluid temperature range)
 - FPM (fluoroelastomer):
-15°C to +100°C (coil class F)
-15°C to +120°C (coil class H)
 - EPDM (ethylene-propylene), 0°C to +100°C
 - CR (chloroprene), 0°C to +80°C
 - PTFE: -15°C to +100°C (coil class F)
-15°C to +120°C (coil class H)
- Oxygen service, FPM disc and seals, see "15-DIGIT PRODUCT CODE"
- WRAS approval, EPDM disc and seals, see "15-DIGIT PRODUCT CODE"
- Magnetic latching versions, reverse polarity DC voltages, see "15-DIGIT PRODUCT CODE FOR MAGNETIC LATCHING VERSION ONLY"
- 15 mm compression-fitting body, supplied with nut and olive, see "15-DIGIT PRODUCT CODE"
- Connector with visual indication and peak voltage suppression or with cable length of 2 m
- Explosionproof enclosures for use in zones 1/21-2/22, categories 2-3 to ATEX Directive 2014/34/EU (See page: 8)

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

⁽²⁾ The minimum ambient temperature of the solenoid valve is determined by the limitations of minimum temperature indicated.



NC function



NO function

Specifications

Specifications															15-DIGIT PRODUCT CODE										
pipe size	orifice size	flow coefficient Kv		operating pressure differential (bar)							power coil (W)		thread type	dimensions / type ⁽¹⁾	brass	stainless steel	voltage code								
				min.	max. (PS)												24 V/50 Hz	48 V/50 Hz	115 V/50 Hz	230 V/50 Hz	24 V/DC	48 V/DC			
					air (*)	water (*)	oil (*)																		
	(mm)	(m³/h)	(l/min)	~	=	~	=	~	=	~	=														
Without manual operator																									
NC - Normally closed, NBR seal and disc																									
1/8	1,2	0,05	0,8	0	51	51	51	41	50	34	8,1	10,6	G NPT	01 01	G262K001S1N00 -	- 8262K012S1N00	FL	FR	FT	F8	H1	H9			
	2,4	0,18	3	0	25	14	22	10	13	10	8,1	10,6	G NPT	01 01	G262K014S1N00 -	- 8262K015S1N00									
	3,2	0,3	5	0	12	8	12	6,5	8	6	8,1	10,6	G NPT	01 01	G262K002S1N00 -	- 8262K006S1N00									
					18	10	17	8	13	8	11,1	18,6	G NPT	01 01	G262K016S1N00 -	- 8262K016S1N00									
	1/4	1,2	0,05	0,8	0	103	68	103	66	103	58	10,1	11,6	G* G* NPT	02 02 02	E262K200S1W00 ⁽²⁾ - -							- E262K214S1W00 ⁽²⁾ 8262K214S1W00 ⁽²⁾		
						151	68	151	66	117	58	10,1	11,6	G* NPT	01 01	E262K019S1N00 -							- 8262K080S1N00		
51						51	51	41	50	34	8,1	10,6	G* NPT	01 01	E262K020S1N00 -	- 8262K086S1N00									
25						14	22	10	11	10	8,1	10,6	G* NPT	01 01	E262K021S1N00 -	- 8262K086S1N00									
2,4		0,18	3	0	34	19	24	13	18	13	11,1	18,6	G* G* NPT	01 02 02	E262K021S1N00 E262K108S1N00 -	- E262K182S1N00 8262K182S1N00									
					40	16	28	16	28	15	10,1	11,6	G* NPT	02 02	E262K109S1N00 -	E262K183S1N00 8262K183S1N00									
					49	41	28	28	28	27	17,1	22,6	G* NPT	02 02	E262K109S1N00 -	E262K183S1N00 8262K183S1N00									
					12	8	12	6,5	6	5,5	8,1	10,6	G* NPT	01 01	E262K022S1N00 -	- 8262K007S1N00									
3,2		0,3	5	0	18	10	17	8	10	7,5	11,1	18,6	G* G* NPT	01 02 02	E262K023S1N00 E262K232S1N00 -	- E262K184S1N00 8262K184S1N00									
					23	7,5	20	7	14	6,5	10,1	11,6	G* NPT	02 02	E262K110S1N00 -	E262K185S1N00 8262K185S1N00									
					34	17	26	17	24	15	17,1	22,6	G* NPT	02 02	E262K111S1N00 -	E262K186S1N00 8262K186S1N00									
					7	5	7	4	4	4	8,1	10,6	G* NPT	01 01	E262K202S1N00 -	E262K220S1N00 8262K220S1N00									
4		0,45	7,5	0	14	3,5	13	3,5	10	3,5	10,1	11,6	G* NPT	02 02	E262K112S1N00 -	E262K187S1N00 8262K187S1N00									
					20	7,5	14	7,5	14	7,5	17,1	22,6	G* NPT	02 02	E262K112S1N00 -	E262K187S1N00 8262K187S1N00									
					6,5	2	6,5	2	6,5	2	10,1	11,6	G* NPT	02 02	E262K208S1N00 -	E262K226S1N00 8262K226S1N00									
					8,5	4	8,5	4	8,5	4	17,1	22,6	G* NPT	02 02	E262K114S1N00 -	E262K188S1N00 8262K188S1N00									
5,6		0,63	10,5	0	3,5	2	3,5	2	2,5	1,9	8,1	10,6	G* NPT	01 01	E262K013S1N00 -	- 8262K036S1N00									
					2	1,6	2	1,5	2	1,3	8,1	10,6	G* NPT	01 01	E262K090S1N00 -	- 8262K038S1N00									
	4				1,5	5	1,5	4	1,3	10,1	11,6	G* NPT	02 02	E262K210S1N00 -	E262K189S1N00 8262K189S1N00										
	6				3	6	3	6	3	17,1	22,6	G* NPT	02 02	E262K212S1N00 -	E262K230S1N00 8262K230S1N00										

⁽¹⁾ For dimensions, see drawing(s) for each construction type on the following page(s).

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

⁽²⁾ UR disc only, fluid temperature 0°C to +60°C, no other elastomer can be used.

Specifications


Specifications															15-DIGIT PRODUCT CODE									
pipe size	orifice size	flow coefficient Kv		operating pressure differential (bar)								power coil (W)		thread type	dimensions / type ⁽¹⁾	brass	stainless steel	voltage code						
				min.	max. (PS)						24 V/50 Hz							48 V/50 Hz	115 V/50 Hz	230 V/50 Hz	24 V/DC	48 V/DC		
					air (*)		water (*)		oil (*)															
	~	=	~		=	~	=	~	=															
(mm)	(m³/h)	(l/min)	Without manual operator																					
NO - Normally open, NBR seal and disc																								
1/8	1,2	0,05	0,8	0	79	44	62	33	55	22	10,1	11,6	G 02	G262K155S1W00 ⁽²⁾	G262K168S1W00 ⁽²⁾	FL	FR	FT	F8	H1	H9			
					51	44	51	38	51	27	10,1	11,6	NPT 02	-	8262K168S1W00 ⁽²⁾									
	2,4	0,18	3	0	18	11	15	9	12	6,5	10,1	11,6	G 02	G262K156S1N00	G262K169S1N00									
					NPT 02	-	8262K169S1N00																	
	3,2	0,3	5	0	11	6,5	10	6,5	8,5	4,5	10,1	11,6	G 02	G262K128S1N00	G262K236S1N00									
					NPT 02	-	8262K236S1N00																	
1/4	1,2	0,05	0,8	0	79	44	62	33	55	22	10,1	11,6	G* 02	E262K129S1N00	G262K237S1N00									
					NPT 02	-	8262K237S1N00																	
	2,4	0,18	3	0	79	44	62	33	55	22	10,1	11,6	G* 02	E262K161S1W00 ⁽²⁾	E262K199S1W00 ⁽²⁾									
					NPT 02	-	8262K199S1W00 ⁽²⁾																	
	3,2	0,3	5	0	51	44	51	38	51	27	10,1	11,6	G* 02	E262K260S1N00	E262K130S1N00									
					NPT 02	-	8262K130S1N00																	
	4	0,47	7,8	0	18	11	15	9	12	6,5	10,1	11,6	G* 02	E262K261S1N00	E262K134S1N00									
					NPT 02	-	8262K134S1N00																	
	5,6	0,72	12	0	11	6,5	10	6,5	8,5	4,5	10,1	11,6	G* 02	E262K262S1N00	E262K138S1N00									
					NPT 02	-	8262K138S1N00																	
	7,1	0,83	13,8	0	6	4	6	3,5	4,5	3	10,1	11,6	G* 02	E262K263S1N00	E262K142S1N00									
					NPT 02	-	8262K142S1N00																	
				3	2	3	1,7	2,5	1,7	10,1	11,6	G* 02	E262K264S1N00	E262K148S1N00										
				NPT 02	-	8262K148S1N00																		
				2	1,3	2	1,1	2	1,1	10,1	11,6	G* 02	E262K265S1N00	E262K152S1N00										
				NPT 02	-	8262K152S1N00																		
With maintained manual operator																								
NC - Normally closed, NBR seal and disc																								
1/4	2,4	0,18	3	0	40	16	28	16	28	15	10,1	11,6	G* 02	E262K108S1N01	E262K182S1N01	FL	FR	FT	F8	H1	H9			
					49	41	28	28	28	27	17,1	22,6	NPT 02	-	8262K182S1N01									
	3,2	0,3	5	0	23	7,5	20	7	14	6,5	10,1	11,6	G* 02	E262K109S1N01	E262K183S1N01									
					34	17	26	17	24	15	17,1	22,6	NPT 02	-	8262K183S1N01									
	4	0,45	7,5	0	23	7,5	20	7	14	6,5	10,1	11,6	G* 02	E262K232S1N01	E262K184S1N01									
					34	17	26	17	24	15	17,1	22,6	NPT 02	-	8262K184S1N01									
	5,6	0,63	10,5	0	23	7,5	20	7	14	6,5	10,1	11,6	G* 02	E262K110S1N01	E262K185S1N01									
					34	17	26	17	24	15	17,1	22,6	NPT 02	-	8262K185S1N01									
	7,1	0,76	12,7	0	14	3,5	13	3,5	10	3,5	10,1	11,6	G* 02	E262K202S1N01	E262K220S1N01									
					20	7,5	14	7,5	14	7,5	17,1	22,6	NPT 02	-	8262K220S1N01									
					14	3,5	13	3,5	10	3,5	10,1	11,6	G* 02	E262K112S1N01	E262K187S1N01									
					20	7,5	14	7,5	14	7,5	17,1	22,6	NPT 02	-	8262K187S1N01									
					20	7,5	14	7,5	14	7,5	17,1	22,6	G* 02	E262K208S1N01	E262K226S1N01									
					8,5	4	8,5	4	8,5	4	17,1	22,6	NPT 02	-	8262K226S1N01									
					6,5	2	6,5	2	6,5	2	10,1	11,6	G* 02	E262K114S1N01	E262K188S1N01									
					8,5	4	8,5	4	8,5	4	17,1	22,6	NPT 02	-	8262K188S1N01									
					4	1,5	5	1,5	4	1,3	10,1	11,6	G* 02	E262K210S1N01	E262K189S1N01									
					6	3	6	3	6	3	17,1	22,6	NPT 02	-	8262K189S1N01									
					4	1,5	5	1,5	4	1,3	10,1	11,6	G* 02	E262K212S1N01	E262K230S1N01									
					6	3	6	3	6	3	17,1	22,6	NPT 02	-	8262K230S1N01									

⁽¹⁾ For dimensions, see drawing(s) for each construction type on the following page(s).

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

⁽²⁾ UR disc only, fluid temperature 0°C to +60°C, no other elastomer can be used.

Configurator - CAD Files



⁽¹⁾ Max. operating pressure limited to 75% of standard value.


⁽²⁾ Check the online configurator for available versions on Emerson.com/asco

⁽³⁾ Search prefix in Emerson.com/asco to get detailed technical information.

Please note that the valve pressure ratings with some of the ATEX enclosures will be reduced.

To obtain the correct pressure rating please check the landing pages of the "2-Way Solenoid Valve DIN Configurator".

⁽⁴⁾ Coils class F only.

		Spare parts kits no. (*)																	
		AC (~)									DC (=)								
			NBR	FPM	FPM (oxygen)	EPDM	EPDM (+WRAS)	CR	PTFE	NBR + UR		NBR	FPM	FPM (oxygen)	EPDM	EPDM (+WRAS)	CR	PTFE	NBR + UR
	E262K013/019/020/ 021/022/023/ 090	M200001	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K08/109/110/ 112/114	M200007	N00	V00	VN0	E00	EM0	J00	T00	-	M200007	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K130	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K134	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K138/142/ 148/152	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K161	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	E262K182/183/184/ 185/187/188/ 189	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	E262K200	M200007	-	-	-	-	-	-	-	W00	M200007	-	-	-	-	-	-	-	W00
	E262K202/208/ 210/212	M200007	N00	V00	VN0	E00	EM0	J00	T00	-	M200007	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K214	M200008	-	-	-	-	-	-	-	W00	M200008	-	-	-	-	-	-	-	W00
	E262K220/226/230	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	E262K232	M200007	N00	V00	VN0	E00	EM0	J00	T00	-	M200007	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K260	M200015	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	N00	V00	VN0	E00	EM0	J00	T00	-
	E262K261	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	-	-	-	-	-	-	-	W00
	E262K262/263/ 264/265	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200032	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K001/002/ 014/016	M200001	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K128	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K129	M200016	N00	V00	VN0	E00	EM0	J00	T00	-	M200032	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K155	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	G262K156	M200015	N00	V00	VN0	E00	EM0	J00	T00	-	M200031	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K168	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	G262K169	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K199	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	G262K236	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	G262K237	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K006/007/012/ 015/036/038	M200003	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K080/086	M200003	N00	V00	VN0	E00	EM0	J00	T00	-	M200005	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K130	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K134	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K138/142/ 148/152	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K168	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	8262K169	M200017	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K182/183/184/ 185/187/188/ 189	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	8262K199	M200021	-	-	-	-	-	-	-	W00	-	-	-	-	-	-	-	-	-
	8262K220/226/230	M200008	N00	V00	VN0	E00	EM0	J00	-	-	M200008	N00	V00	VN0	E00	EM0	J00	-	-
	8262K236	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200033	N00	V00	VN0	E00	EM0	J00	T00	-
	8262K237	M200018	N00	V00	VN0	E00	EM0	J00	T00	-	M200034	N00	V00	VN0	E00	EM0	J00	T00	-

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

Magnetic latching version

fluids (*)	temperature range (TS)	seal materials (*)
water	0°C to +85°C	EPDM

Electrical characteristics

Coil insulation class

F (DC)

Standard voltages

DC (=) : 3V - 6V - 9V - 12V

operator ambient temperature range (TS)	power ratings		replacement coil ⁽¹⁾	
	hot/cold =		=	
	(W)			
(°C)	640	641/642/643/644	6 V DC	12 V DC
0 to +40	2,5	-	400927-003	400927-005
	-	6	400927-007	400927-014

⁽¹⁾ All coils 400 series are not UL & CSA approved.




Specifications


Specifications									15-DIGIT PRODUCT CODE						
pipe size	orifice size	flow coefficient Kv		operating pressure differential (bar)		power coil (W)	thread type	dimensions / type ⁽²⁾	brass	voltage code					
				min.	max. (PS)					3 V/DC	6 V/DC	9 V/DC	12 V/DC	24 V/DC	
	water (*)														
	=	=													
Without manual operator															
EPDM seal and disc															
15 mm compression fittings	1,2	0,05	0,8	0	10	2,5	H	03	H262K640S1EM0	CD	E7	E8	F3	F1	
	2,0	0,15	2,5	0	10	6	H	03	H262K641S1EM0						
	3,2	0,30	5,0	0	3	6	H	03	H262K642S1EM0						
	4	0,45	7,5	0	2	6	H	03	H262K643S1EM0						
	6.7	0.82	13.7	0	0.7	6	H	03	H262K644S1EM0						

⁽²⁾ For dimensions, see drawing(s) for each construction type on the following page(s).


(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

Configurator - CAD Files



Spare parts kits no. (*)			
DC (=)			
EPDM (+ WRAS)			
	H262K640 / H262K641 H262K642 / H262K643 H262K644	M200001	EM0

(*) Ensure that the compatibility of the fluids in contact with the materials is verified.

		Accessories code
	Mounting bracket Steel version (AISI 1010 / 1.1121)	M200094A00
	Mounting bracket Stainless steel version (AISI 304 / 1.4301)	M200095A00

Installation

- The solenoid valves can be mounted in any position without affecting operation
- Solenoid valves have 2 mounting holes in body
- Thread connection “E” applicable for 1/4 have standard thread according to ISO 228/1 and ISO 7/1. Thread connection “G” applicable for 1/8, have standard thread according to ISO 228/1
- Thread connection “H” have standard thread = NPT (SAE 71051)
- Thread connection “H” have 1/2” male ‘G’ thread according to BS 2779 plus cap-nut and olive
- Installation/maintenance instructions are included with each valve

Dimensions (mm), Weight (kg)





Configurator - CAD Files



TYPE 01
Electrical interface “S1”
Epoxy moulded
IEC 335 / ISO 4400
IP65

1/8, power coil 8,1 W / 10,6 W and 11,1 W / 18,6 W

1/4, power coil 8,1 W / 10,6 W and 11,1 W / 18,6 W



type	pipe size	A	B	C	D	E	F	G	H	X	weight ⁽¹⁾
01	1/8	88	51	30	30	43	62	71	88	26	0,30
	1/4	88	51	30	40	43	65	75	92	30	0,42

⁽¹⁾ Incl. coil(s) and connector(s).

- ① 2 mounting holes:
M5 dia., depth 6,5 mm (1/8)
M5 dia., depth 7,5 mm (1/4)
- ② Manual operator location

Dimensions (mm), Weight (kg)


Configurator - CAD Files



TYPE 02
Electrical interface "S1"
Epoxy moulded
IEC 335 / ISO 4400
IP65

NC: 1/4, power coil 10,1 W / 11,6 W and 17,1 W / 22,6 W

NO: 1/8-1/4, power coil 10,1 W / 11,6 W






type	pipe size	A	B	C	D	E	F	G	H	J	K	X	weight ⁽¹⁾
02	1/8 (NO)	96	59	34	30	52	67	75	88	17,5	15	26	0,50
	1/4 (NC)	95	57	33	40	50	69	78	96	22	22	30	0,60
	1/4 (NO)	96	59	34	40	52	69	78	96	22	22	30	0,62

⁽¹⁾ Incl. coil(s) and connector(s).

- ① 2 mounting holes:
M5 dia., depth 7,5 mm
(1/4)
- ② Manual operator location.




Electrical interface "S1"
Epoxy moulded
IEC 335 / ISO 4400
IP65



Magnetic Latching version


- ① 2 mounting holes:
190-24 UNC-2B, depth 6 mm

weight ⁽¹⁾
0,45



Mounting brackets
Steel or stainless steel

M200094A00 / M200095A00



A.P.O. - ELMOS v.o.s., Pražská 90, 509 01 Nová Paka, Tel.: +420 493 504 261, E-mail: apo@apoelmos.cz, Internet: www.apoelmos.cz